





ALUMINUM WELDMENT CONNECTORS DOUBLE CABLE TO FLAT PAD

SECTION

18-10



Continued from previous page

CATALOG NUMBER	PAD STYLE	CABLE SIZE		CONDUCTOR DIAMETER IN INCHES	HOLE DIAMETER	DIMENSIONS IN INCHES		
		AAC	ACSR			A	B	C
18-752	B	600(37)-650(91)	556.5(24/7)-556.5(30/7)	.884-.953	1	5	1 5/8	1/2
18-753	C	600(37)-650(91)	556.5(24/7)-556.5(30/7)	.884-.953	1	5	1 5/8	1/2
18-754	D	600(37)-650(91)	556.5(24/7)-556.5(30/7)	.884-.953	1	6	1 3/4	3/4
18-758	B	700(61)-800(61)	605(26/7)-636(30/19)	.954-1.039	1 1/8	5	1 1/2	1/2
18-759	C	700(61)-800(61)	605(26/7)-636(30/19)	.954-1.039	1 1/8	5	1 1/2	1/2
18-760	D	700(61)-800(61)	605(26/7)-636(30/19)	.954-1.039	1 1/8	6	1 3/4	3/4
18-761	B	817.5(61)-954(61)	653.9(18/3)-795(24/7)	1.040-1.140	1 3/16	5 3/8	2	1/2
18-762	C	817.5(61)-954(61)	653.9(18/3)-795(24/7)	1.040-1.140	1 3/16	5 3/8	2	5/8
18-763	D	817.5(61)-954(61)	653.9(18/3)-795(24/7)	1.040-1.140	1 3/16	6 3/8	2	1
18-767	B	1000(61)-1113(61)	954(45/7)-954(54/7)	1.141-1.216	1 1/4	5 1/2	2	1/2
18-768	C	1000(61)-1113(61)	954(45/7)-954(54/7)	1.141-1.216	1 1/4	5 1/2	2	5/8
18-769	D	1000(61)-1113(61)	954(45/7)-954(54/7)	1.141-1.216	1 1/4	6 1/2	2	1
18-773	B	1200(91)-1272(61)	1033.5(54/7)-1113(54/19)	1.217-1.300	1 3/8	5 1/2	2	1/2
18-774	C	1200(91)-1272(61)	1033.5(54/7)-1113(54/19)	1.217-1.300	1 3/8	5 1/2	2	5/8
18-775	D	1200(91)-1272(61)	1033.5(54/7)-1113(54/19)	1.217-1.300	1 3/8	6 3/8	2	1
18-785	B	1351.5(61)-1590(61)	1272(45/7)-1431(45/7)	1.301-1.454	1 1/2	6 3/4	2 3/8	1
18-786	C	1351.5(61)-1590(61)	1272(45/7)-1431(45/7)	1.301-1.454	1 1/2	6 3/4	2 3/8	1
18-787	D	1351.5(61)-1590(61)	1272(45/7)-1431(45/7)	1.301-1.454	1 1/2	6 3/8	2	1
18-787-SP(1700AAC)	D	1600(127)-1700(127)	1431(54/19)-1510.5(54/19)	1.455-1.506	1 9/16	6 3/8	2	1
18-787-SP(1590ACSR)	D	1750(127)	1590(54/19)	1.507-1.545	1 5/8	7 1/8	3	1 1/8
18-787-SP(2000AAC)	D	2000(91)(127)	1780(84/19)	1.546-1.680	1 3/4	7 1/8	3	1 1/8
18-787-SP(2156ACSR)	D	2250(91)	2034(72/7)-2167(72/7)	1.681-1.801	1 7/8	7 1/8	3	1 1/8
18-787-SP(2500AAC)	D	2500(127)	2312(76/19)-2515(76/19)	1.802-1.880	2	7 1/8	3	1 1/8
18-787-SP(3000AAC)	D	3000(127)		1.890-1.998	2 1/8	7 1/8	3	1 1/8
18-787-SP(3500AAC)	D	3500(127)		1.999-2.159	2 1/4	7 1/8	3	1 1/8